

Model	XS6	XS8	XS10
Pixel Pitch(mm)	6	8	10
Pixel Density(pixels/m ²)	27,777	15,625	10,000
LED type	SMD2727	SMD3535	SMD3535
Viewing Angle	H140°/V140°	H140°/V140°	H140°/V140°
Brightness(nits)	6,000	6,500	7,000
Refresh Rate	≥1,200Hz	≥1,200Hz	≥1,200Hz
Module Size(mm)	288 x 288	288 x 288	320 x 320
Module pixels	48 x 48	36 x 36	32 x 32
Cabinet Size(mm)	864 x 864 x 210	864 x 864 x 210	960 x 960 x 210
Cabinet pixels	128 x 128	120*120	96 x 96
Cabinet Type and Material	Steel/Aluminum	Steel/Aluminum	Steel/Aluminum
Cabinet Weight (kgs)	38(Aluminum)	45(Aluminum)	45(Aluminum)
Working Voltage	110/220 AC	110/220 AC	110/220 AC
Avg. Power Consumption (W/m ²)	251	265	338
Max. Power Consumption (W/m ²)	754	796	1,015
Service Access	Front	Front	Front
IP Grade (Front/Rear)	IP65/IP54	IP65/IP54	IP65/IP54
Operating Temp/Humidity	-20°C~65°C 10-90%RH	-20°C~65°C 10-90%RH	-20°C~65°C 10-90%RH
Storage Temp/Humidity	-30°C~70°C 10-90%RH	-30°C~70°C 10-90%RH	-30°C~70°C 10-90%RH
Lifetime(Normal Temp)	≥100,000H	≥100,000H	≥100,000H

XS SERIES



AUDIOVISUAL
contact@jmmaudio.net