

Tile	Q10	Q16
Pixel Pitch(mm)	10.16mm	16mm
Pixel Density(pixels/m ²)	9,687	3,906
LED type	DIP346	DIP346
Viewing Angle	H120°/V60°	H120°/V60°
Brightness(nits)	6,500	8,000
Refresh Rate	≥3,000Hz	≥3,000Hz
Module Size(mm)	304.8 x 304.8 (1 feet x 1 feet)	304.8 x 304.8 (1 feet x 1 feet)
Cabinet size(mm)	1,219 x 914 x 46 (4 feet x 3 feet)	914 x 914 x 46 (4 feet x 3 feet)
Cabinet Type and Material	Metal plate	Metal plate
Cabinet Weight (kgs)	35	35
Working Voltage	110/220 AC	110/220 AC
Avg. Power Consumption (W/m ²)	158	193
Max. Power Consumption (W/m ²)	473	579
Service Access	Rear and front	Rear and front
IP Grade (Front/Rear)	IP65/IP54	IP65/IP54
Operating Temp/Humidity	-20°C~65°C 10-90%RH	-20°C~65°C 10-90%RH
Storage Temp/Humidity	-30°C~70°C 10-90%RH	-30°C~70°C 10-90%RH
Lifetime(Normal Temp)	≥100,000H	≥100,000H

Q SERIES



AUDIOVISUAL
contact@jmmaudio.net