

Type 2-way full range Component 10" Woofer +1.5"+ horn Nominal Impedance  $8\Omega$ RMS Power Handling 230W Peak Power Handling 460W Frequency Response 58Hz-20KHz Sensitivity(1W/1M) 100dB Max. SPL 124dB Recommended Amp Makro 350 or JT8 for 2pcs Dispersion 60°H×40°V Horn throat size 1"(25mm) Voice coil size 2"(34mm) Crossover 1.8KHz Dimension HWD(mm) 530×328×280 Shipping HWD(mm) 595×420×370 (0.09CBM NW/GW(Kg) 15.5/17.5







Component 6.5"+1" Nominal Impedance 8Ω **RMS** Power Handling 60W Peak Power Handling 120W Frequency Response 80Hz-20KHz Sensitivity(1W/1M) 95dB Max, SPI 115dB Recommended Makro 704 4pcs Amp Makro 708 8 pcs Dispersions 50°H×55° V Dimension HWD(mm) 310×210×200 Shipping HWD(mm) 410×525×290 (0.06CBM/2pcs) NW/GW(Kg) 9/11.5(2pcs/ctn)

2-way full range



JP6.5- BAR SPEAKER



Type



JS10 is designed for indoor use , bar, restaurant, etc.

Loaded with JMM High Frequency driver and a 90 degree rotatable horn, it gives high dynamic acoustic pressure levels and sound clarity. The rotatable horn also makes installation optimal.

JP6.5 our best selling small speaker, 2-way with 6.5' bass woofer, also availabl in 5' and 8' woofer. many speakers look like this but none have the bass response and crisp clarity of the JP6.5

Contact@jmmaudio.net http://www.jmmaudio.net/ Tel: +852 609 77224



908-9 9/F TAI YAU BUILDING 181 JOHNSTON ROAD WANCHAI HONG KONG HONG KONG

JMM Audio is a subsidiary of 777Limited